

AGROPLUS F Keyline



DEUTZ-FAHR
AGROPLUS F Keyline
55 - 65 - 75 - 80.4



4 models from 55 HP to 75 HP. Equipped for your special applications.


The Agropius F Keyline is the perfect compact tractor especially for working in orchards or on smaller open fields. It is equipped with simple and innovative mechanical controls, all-wheel braking with wet disc brakes and separate valve and offers top ergonomomy due to the rational control layout. With its great price content relation, the Agropius F Keyline is your key to more efficiency.

Technical Data		Agropius F Keyline			
		55	65	75	80.4
ENGINE					
Emissions		Tier3	Tier3	Tier3	Tier3
Manufacturer		SDF 1000 Series	SDF 1000 Series	SDF 1000 Series	SDF 1000 Series
Cylinders / Displacement	n°/cc	3/3000	3/3000	3/3000	4/4000
Turbocharged intake		●	●	-	-
Turbo intercooler intake		-	-	●	●
Max. power (@ 2.000 rpm)	kW/HP	40.5/55	45.6/62	53/72	55/75
Rated power (@ 2.200 rpm)	kW/HP	40.5/55	45.6/62	53/72	55/75
Max. engine speed (rated)		2200	2200	2200	2200
Max. torque	Nm	213	240	265	285
Mechanical engine control		●	●	●	●
Fuel tank capacity	L	65	65	65	65
Torque backup	%	21	21	15	19
TRANSMISSION					
Synchronised		●	●	●	●
Mechanical shuttle		●	●	●	●
N° of speeds, 4 gears	n°	8+8	8+8	8+8	8+8
N° of speeds, 5 gears	n°	10+10	10+10	10+10	10+10
N° of speeds with creeper	n°	15+15	15+15	15+15	15+15
Max. speed	km/h	40	40	40	40
Min. speed (without / with supercreeper)		2.4/0.38	2.4/0.38	2.4/0.38	2.4/0.38
PTO					
Mechanical dry clutch, single		●	●	●	●
PTO 540		●	●	●	●
PTO 540 / 540ECO		○	○	○	○
Groundspeed PTO		○	○	○	○
FRONT AXLE					
Mechanical differential lock and 4 WD engagement		●	●	●	●
Steering angle / turning circle 4WD	degrees/mm	55/3500	55/3500	55/3500	55/3600
BRAKES					
4-wheel brake		●	●	●	●
Braking system with wet brake discs		●	●	●	●
Mechanical parking brake		●	●	●	●
STEERING					
Hydrostatic steering with independent pump		●	●	●	●
Steering and transmission pump delivery	L/min	18	18	18	18
HITCH					
Category		II	II	II	II
Mechanical rear lift		●	●	●	●
Rear lifting capacity (STANDARD version)	kg	3050	3050	3050	3050
Rear lifting capacity (COMPACT version)	kg	2700	2700	2700	2700
HYDRAULIC SYSTEM					
Main pump delivery	L/min	42	42	42	42
Mechanical spool valves (std/opt)	n° of ways	4 / 6	4 / 6	4 / 6	4 / 6
Open-centre hydraulic system		●	●	●	●
Mechanical distributor engagement		●	●	●	●
DRIVING POSITION					
Folding front roll bar		●	●	●	●
Driver seat with mechanical suspension		●	●	●	●
Analogue instrumentation		●	●	●	●
DIMENSIONS & WEIGHT (4 WD)					
Standard front - rear tyres		280 / 70 R16" - 360 / 70 R24"	280 / 70 R16" - 360 / 70 R24"	280 / 70 R16" - 360 / 70 R24"	280 / 70 R16" - 360 / 70 R24"
Wheelbase	mm	1996	1996	1996	2126
Length	mm	3442	3442	3442	3573
Overall width front/rear	mm	1462 / 1466	1462 / 1466	1462 / 1466	1462 / 1466
Front track	mm	1166	1166	1166	1166
Rear track	mm	1091	1091	1091	1091
Height at safety frame	mm	2319	2319	2319	2319
Height (Dashboard / Rear mudguards)	mm	1387 / 1211	1387 / 1211	1387 / 1211	1387 / 1211
Max. admissible load	kg	4200	4200	4200	4350
Weight	kg	2200	2200	2200	2300
Homologated weight	kg	2450	2450	2450	2600

● STD ○ OPT - Not available

Dealer

To discover more please contact your dealer or visit deutz-fahr.com.

DEUTZ-FAHR is a brand of  SDF



The technical specifications and images herein are purely indicative. DEUTZ-FAHR reserves the right to update this information at any time without notice.